



NOTES:
 1) RECOMMENDED PANEL HOLE SEE "DETAIL A"
 2) RECOMMENDED PANEL THICKNESS 1.2mm TO 2.6mm

DIMENSIONS ARE IN MILLIMETERS.

DRAWN BY: S. BOUJLOV	DATE: 2/04/14	UNLESS NOTED OTHERWISE, DIMENSIONS ARE IN MILLIMETERS, INCHES ARE IN SQUARE BRACKETS, AND TOLERANCES APPLY AS SHOWN BELOW.		 OZ Optics 219 WESTBROOK ROAD OTTAWA, ONTARIO CANADA K0A 1L0 www.ozoptics.com	PART BARCODE #: 9
CHECKED BY:	DATE:	INCHES BASIC DIMENSION .XX .XXX BELOW 4 ±.01 ±.005 OVER 4 ±.02 ±.01			DESC. FC Adaptor without Flange
M/S CHECKED BY:	DATE:	MILLIMETERS BASIC DIMENSION .X .XX BELOW 101.6 ±.25 ±.10 OVER 101.6 ±.50 ±.20		PART NO. SMPC-03-SP	
APVD BY:	DATE:	ANGULAR DIMENSIONS BASIC DIMENSION X X.X ALL ANGLES ±2.5° ±0.5°			REV N/A
PROJECTION: 	CONFIDENTIAL THIS PRINT IS THE EXCLUSIVE PROPERTY OF OZ OPTICS AND MUST BE RETURNED UPON REQUEST. UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.		SURFACE FINISH MILLED 125u PROFILED 63u	SIZE: B DWG.# 3000-0250 SHEET 1 OF 1 SCALE: 5:1	