


NOTES:
 1) RECOMMENDED PANEL HOLE SEE "DETAIL A"
 2) RECOMMENDED PANEL THICKNESS
 1.2mm TO 2.6mm

DIMENSIONS ARE IN MILLIMETERS.

DRAWN BY: S. BOUJLOV		DATE: 2/04/14		UNLESS NOTED OTHERWISE, DIMENSIONS ARE IN MILLIMETERS, INCHES ARE IN SQUARE BRACKETS, AND TOLERANCES APPLY AS SHOWN BELOW.				219 WESTBROOK ROAD OTTAWA, ONTARIO CANADA K0A 1L0		PART BARCODE #: 14	
CHECKED BY:		DATE:		INCHES		MILLIMETERS		DESC: ST Sleeve thru Connectors Adaptor for SM		PART NO.:	
M/S CHECKED BY:		DATE:		BASIC DIMENSION		DECIMAL PLACES		BULK-08-S		REV: N/A	
APVD BY:		DATE:		BELOW 4		.XX .XXX		SIZE: B		DWG.# 3000-0254	
PROJECTION:		DATE:		OVER 4		.X .XX		SHEET 1 OF 1		SCALE: 4:1	
CONFIDENTIAL THIS PRINT IS THE EXCLUSIVE PROPERTY OF OZ OPTICS AND MUST BE RETURNED UPON REQUEST. UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.		DATE:		ANGULAR DIMENSIONS		ALL ANGLES		SURFACE FINISH		MILLED 125u	
		DATE:		BASIC DIMENSION		X .X		PROFILED 63u			