


NOTES:
 1) RECOMMENDED PANEL HOLE SEE "DETAIL A"
 2) RECOMMENDED PANEL THICKNESS 1.2mm TO 2.6mm

DIMENSIONS ARE IN MILLIMETERS.

| | | | | | |
|-------------------------|---|---|--|---|--|
| DRAWN BY: S. BOUJLOV | DATE: 2/04/14 | UNLESS NOTED OTHERWISE, DIMENSIONS ARE IN MILLIMETERS, INCHES ARE IN SQUARE BRACKETS, AND TOLERANCES APPLY AS SHOWN BELOW. | |  OZ Optics 219 WESTBROOK ROAD OTTAWA, ONTARIO CANADA K0A 1L0 www.ozoptics.com | PART BARCODE #: 32624 |
| CHECKED BY: | DATE: | INCHES BASIC DIMENSION .XX .XXX BELOW 4 ±.01 ±.005 OVER 4 ±.02 ±.01 MILLIMETERS BASIC DIMENSION .X .XX BELOW 101.6 ±.25 ±.10 OVER 101.6 ±.50 ±.20 | | | DESC. PM Sleeve-Thru Adapter |
| M/S CHECKED BY: | DATE: | ANGULAR DIMENSIONS BASIC DIMENSION X X.X ALL ANGLES ±2.5° ±0.5° | | PART NO. PMPC-03-"D"-SP | REV N/A |
| APVD BY: | DATE: | SURFACE FINISH MILLED 125u PROFILED 63u | | SIZE: B | DWG.# 3000-0269 |
| PROJECTION: |  | CONFIDENTIAL THIS PRINT IS THE EXCLUSIVE PROPERTY OF OZ OPTICS AND MUST BE RETURNED UPON REQUEST. UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED. | | SHEET 1 OF 1 | SCALE: 5:1 |