



NUMERICAL APERTURE	0.29
EFFECTIVE FOCAL LENGTH	6.0mm

- NOTES :**
- 1) LENS 1: CaF2 GLASS
 - 2) LENS 2: UV GRADE FUSED SILICA
 - 3) SURFACE QUALITY PER MIL-0-13830
 - 4) COATING: R1: AR FOR R<0.5% 300nm-400nm
R2: AR FOR R<0.5% 300nm-400nm

ALL DIMENSIONS ARE IN MILLIMETERS		A	N/A	ORIGINAL ISSUE	C.M.	01-OCT-2019	
DRAWN BY: P. SUMMERS	DATE: 10/1/2019	REV.	ECR REF#	DESCRIPTION	ENG. BY	DATE	
CHECKED BY:	DATE:	UNLESS NOTED OTHERWISE, DIMENSIONS ARE IN MILLIMETERS, INCHES ARE IN SQUARE BRACKETS, AND TOLERANCES APPLY AS SHOWN BELOW.				PART BARCODE # 15550	
M/S CHECKED BY:	DATE:	INCHES				219 WESTBROOK ROAD OTTAWA, ONTARIO CANADA K0A 1L0	
APVD BY:	DATE:	MILLIMETERS				www.ozoptics.com	
PROJECTION:		ANGULAR DIMENSIONS				DESC. DOUBLET LENS f=6mm OD=3mm AR COATED FOR 300 TO 400nm	
CONFIDENTIAL THIS PRINT IS THE EXCLUSIVE PROPERTY OF OZ OPTICS AND MUST BE RETURNED UPON REQUEST. UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.		SURFACE FINISH				PART NO. ACH-F6AG-D3-300/400	
		MILLED		PROFILED	SIZE:	REV A	
		125u		63u	B	DWG.# 4000-0243	
					SHEET 1 OF 1		
					SCALE: 16:1		